

# TENSIONATORE PER REGGIA COMPOSITA da 16 A 32 mm

ZAPAK®



## Latest technology

- **Brushless Motor** – Zapak's latest 4th generation Brushless Motor generates a very steady output to ensure consistent and reliable tensioning for your cord strapping needs.
- **Bosch 18V 4.0Ah Li-Ion Battery** – rechargeable battery with Charge Level Indicator (CLI), can strap up to 350 cycles per fully charged battery.

## Powerful & Reliable

- **Tensioning Force** – Max. Tension **800 daN**.
- **Industrial Grade Tool** – we are the original manufacturer of the ZP-CT32A. The tensioner is completely designed and newly molded for Industrial Grade use.
- The ZP-CT32A is NOT made by simply attaching a typical electric drill to a manual windlass tensioner.

## Smart & Easy

- **Electronic Control Unit (ECU)** – 3 pre-programmed tension modes: Auto/Semi/Manual. And tension torque (1-6 levels) are electronically controlled (No need to hand turn a manual clutch to change torque).
- **Designated Quick Reverse Button (QRB)** – pre-programmed auto reverse button allows for easy reverse turning of the windlass for quick tool removal after tension (without having to switch back and forth on the Forward/Reverse button on a typical electric drill).
- **Cutter** – designed to cut both **Composite and Woven cord straps**.

## Ergonomic

- **6 Degree Angle on the handle bar** – ergonomically designed to lessen wrist fatigue while tensioning on a flat surface, and during vertical operation.
- **Low Center of Gravity design** – reduced the overall height of the tensioner to lessen operating fatigue during horizontal & vertical operation.

## Specification

- Strap Type: Composite & Woven cord strapping
- Strap Width: 19 - 32mm; Thickness: 0.85~1.65mm
- Tensioning Force: 6 settings (300 - 800 daN)
- Tensioning Speed: 35 mm/s
- Weight including battery: approx. 3.6 kg

## Safety

- Single-handed operation **conforms to CE safety directive** and meets RoHS requirements.
- Li-Ion battery **complies with UN38.3** safety requirements.



ISO 9001: 2015

**Veneta Imballaggi S.r.l.**

37050 - Villafontana di Oppeano (Vr) - Via Villafontana, 291  
T. +39 045 714 5181 / F. +39 045 698 9047  
[info@venetaimballaggi.eu](mailto:info@venetaimballaggi.eu) - [www.venetaimballaggi.eu](http://www.venetaimballaggi.eu)



**VENETAIMBALLAGGI**  
PROTEGGE I TUOI PRODOTTI